



# PENDANT LED LUMINAIRE

# **BL46-V Series**

Techlumen COBO series LED luminaires are **pendant with adjustable direction**.

They are made of aluminum and painted with electrostatic powder paint in any RAL color.

COBO are produced in 6W-25W power outputs and in color temperatures of 2700K to 6500K with efficacy up to 182 lm / W.

Additionally they are available in special versions for illuminating bread and meat products.

They come with 5 years warranty.









## **Manufactured in Greece**



#### Dimensions



#### Pros

- Low working temperature
- It produces little heat compared to other types of lighting
- Requires no maintenance
- Long life 5 years warranty
- Easy installation
- High reliability
- Excellent performance with low power consumption
- High brightness
- High color rendering up to 97 CRI
- Instant start immediate termination
- It does not emit UV or IR radiation
- Does not contain mercury
- Resistance to shock and vibration

### Applications

- Retail
- Cafe Bar
- Galleries
- Restaurants

Туре	СОВО
Luminus Power	565 Jm - 4227 Jm
Power	6W - 25W
Driver	Meanwell
Dimming	Optional
LED Chip	Bridgelux V & Vero
Consumption	0.006 - 0.026 KWh/h
Ambient Temperature	-30 °C - + 40 °C
Efficacy	95 - 182lm/W
Power Factor	0,95
CRI	70 - 90
CCT	2700 - 6500K
IP Rating	IP20
Body	Alluminium
Finishing	Any RAL
Dimensions	Ф220mm - H=140mm
Weight	1,4 Kg
Warranty	5 years
Approvals:	CE, EN 60598-1,
	EN 13032.01
	EN 61439-1:2009
	EN 61543:1995
	2006/95/EC
	2004/108/EC
	EN 60598-2-2
	Rohs

COBO V	ersions			-	
Watt	Code	ССТ	CRI	Lumen	Lm/W
	COBO-927-6	2700	90	590	95
6W	COBO-827-6	2700	80	740	119
	COBO-930-6	3000	90	625	100
	COBO-830-6	3000	80	785	126
	COBO-940-6	4000	90	670	108
	COBO-840-6	4000	80	820	132
	COBO-850-6	5000	80	820	132
	COBO-750-6	5000	70	865	139
	COBO-827-9	2700	80	1332	146
	COBO-927-9	2700	90	1111	122
	COBO-830-9	3000	80	1388	153
	COBO-930-9	3000	90	1152	127
	COBO-835-9	3500	80	1430	157
	COBO-935-9	3500	90	1194	131
9W	COBO-840-9	4000	80	1444	159
	COBO-940-9	4000	90	1236	136
	COBO-750-9	5000	70	1580	174
	COBO-850-9	5000	80	1486	163
	COBO-950-9	5000	90	1264	139
	COBO-757-9	5700	70	1525	168
	COBO-857-9	5700	80	1511	166
	COBO-765-9	6500	70	1553	171
	COBO-865-9	6500	80	1538	169
	COBO-827-12	2700	80	1768	145
	COBO-927-12	2700	90	1473	121
	COBO-830-12	3000	80	1841	151
	COBO-930-12	3000	90	1529	125
	COBO-835-12	3500	80	1896	156
	COBO-935-12	3500	90	1584	130
	COBO-840-12	4000	80	1915	157
	COBO-940-12	4000	90	1639	134
	COBO-750-12	5000	70	2096	172
12W	COBO-850-12	5000	80	1970	162
	COBO-950-12	5000	90	1676	137
	COBO-757-12	5700	70	2022	166
	COBO-857-12	5700	80	2003	164
	COBO-765-12	6500	70	2059	169
	COBO-865-12	6500	80	2041	167

MEAT & BAKERY SPECIAL VERSIONS

1750 80

2500 80

1750 80

80

2500

1141 81

1848 132

1557 78

2522 126

COBO-M-14

COBO-B-14

COBO-M-20


COBO-B-20


14W


20W

	COBO Versions					
	Watt	Code	ССТ	CRI	Lumen	Lm/W
		COBO-827-17	2700	80	2620	154
	17W	COBO-927-17	2700	90	2183	128
		COBO-830-17	3000	80	2729	160
		COBO-930-17	3000	90	2265	133
		COBO-835-17	3500	80	2811	165
		COBO-935-17	3500	90	2347	138
		COBO-840-17	4000	80	2838	166
		COBO-940-17	4000	90	2429	142
		COBO-750-17	5000	70	3106	182
		COBO-850-17	5000	80	2920	171
		COBO-950-17	5000	90	2485	146
		COBO-757-17	5700	70	2997	176
		COBO-857-17	5700	80	2908	166
		COBO-765-17	6500	70	2989	171
		COBO-865-17	6500	80	2812	156
	25W	COBO-827-25	2700	80	3565	145
		COBO-927-25	2700	90	2971	121
		COBO-830-25	3000	80	3714	151
		COBO-930-25	3000	90	3083	126
		COBO-835-25	3500	80	3825	156
		COBO-935-25	3500	90	3194	130
		COBO-840-25	4000	80	3862	157
		COBO-940-25	4000	90	3305	135
		COBO-750-25	5000	70	4227	172
		COBO-850-25	5000	80	3973	162
		COBO-950-25	5000	90	3382	138
		COBO-757-25	5700	70	4078	166
		COBO-857-25	5700	80	4042	165
		COBO-765-25	6500	70	4153	169
		COBO-865-25	6500	80	4116	168

		Б.	
Polar	Intensity	Diagram	







AFOI TSIOLAKI OE Industrial Zone of Thessaloniki Greece

T: +302310 798 335 F: +302310 799 868 e-mail: info@techlumen.gr www.techlumen.gr







