



## Linear LED

### L-SP Series

L-SP linear LED luminaires provide powerful lighting with minimal consumption.

They are available in versions of 3000K - 6500K and in various lengths, up to 282cm and 21980lm.

They have 5 years warranty.

L-SP LED fixtures are also produced with additional emergency function, with 1h or 3h or emergency operation during power failures.

DALI

0-10V

Em 3h

BLUE  
TOOTH

DIM to  
WARM


TUNABLE  
CCT



Manufactured in Greece



### Dimensions



### Applications


- Warehouses
- Supermarkets
- Offices
- Factories

Type	L-SP
Luminous Flux	2072 lm - 21980 lm
Power	13W - 128W
Ambient Temperature	-30 °C - + 50 °C
Efficacy	159 - 172 lm/W
Power Factor	0,95
CRI	80
CCT	3000K - 6500K
IP Rating	IP30
IK Rating	IP07
Body	Aluminium
Dimensions	51mm x 75mm x (300 - 2820)mm
Weight	0.6 - 4.5 Kg
Finishing	Powder coating - RAL color selection
Warranty	5 years
Compliances	CE EN 60598-1:2021+A11:2022 EN 60598-2-1:2022 EN 60598-2-2:2023 EN IEC 61000-3-2:2019+A1:2021 EN 61000-3-3:2013+A2:2021 EN 61547:2020 EN 55015:2019+A11:2020 EN 62471:2008 IEC/TR 62778:2014 EN 62493:2015+A1:2022 EN 63000:2018 Directive (LVD) 2014/35/EU Directive (EMC) 2014/30/EU Directive (RoHS) 2011/65/EC Directive (REACH) 2015/863/EU Directive (GPS) 2015/863/EU Directive (EuP) 2001/95/EC

L-SP Versions						
Watt	Code	CCT	CRI	Lumen	Lm/W	
<b>13W - 30cm</b>	L-SP-30-830-13	3000	80	2072	159	
	L-SP-30-840-13	4000	80	2198	169	
	L-SP-30-850-13	5000	80	2184	168	
<b>26W - 60cm</b>	L-SP-30-865-13	6500	80	2155	166	
	L-SP-60-830-26	3000	80	4144	159	
	L-SP-60-840-26	4000	80	4396	169	
<b>39W - 85cm</b>	L-SP-60-850-26	5000	80	4368	168	
	L-SP-60-865-26	6500	80	4310	166	
	L-SP-85-830-39	3000	80	6216	159	
<b>51W - 115cm</b>	L-SP-85-840-39	4000	80	6594	169	
	L-SP-85-850-39	5000	80	6552	168	
	L-SP-85-865-39	6500	80	6465	166	
<b>64W - 142cm</b>	L-SP-115-830-51	3000	80	8288	163	
	L-SP-115-840-51	4000	80	8792	172	
	L-SP-115-850-51	5000	80	8736	171	
<b>77W - 170cm</b>	L-SP-115-865-51	6500	80	8620	169	
	L-SP-142-830-64	3000	80	10360	162	
	L-SP-142-840-64	4000	80	10990	172	
<b>89W - 200cm</b>	L-SP-142-850-64	5000	80	10920	171	
	L-SP-142-865-64	6500	80	10775	168	
	L-SP-225-830-102	3000	80	16576	163	
<b>102W - 225cm</b>	L-SP-225-840-102	4000	80	17584	172	
	L-SP-225-850-102	5000	80	17472	171	
	L-SP-225-865-102	6500	80	17240	169	
<b>115W - 255cm</b>	L-SP-255-830-115	3000	80	18648	162	
	L-SP-255-840-115	4000	80	19782	172	
	L-SP-255-850-115	5000	80	19656	171	
<b>128W - 282cm</b>	L-SP-255-865-115	6500	80	19395	169	
	L-SP-282-830-128	3000	80	20720	162	
	L-SP-282-840-128	4000	80	21980	172	
<b>128W - 282cm</b>	L-SP-282-850-128	5000	80	21840	171	
	L-SP-282-865-128	6500	80	21550	168	

L-SP Versions						
Watt	Code	CCT	CRI	Lumen	Lm/W	
<b>77W - 170cm</b>	L-SP-170-830-77	3000	80	12432	161	
	L-SP-170-840-77	4000	80	13188	171	
	L-SP-170-850-77	5000	80	13104	170	
<b>89W - 200cm</b>	L-SP-170-865-77	6500	80	12930	168	
	L-SP-200-830-89	3000	80	14504	163	
	L-SP-200-840-89	4000	80	15386	173	
<b>102W - 225cm</b>	L-SP-200-850-89	5000	80	15288	172	
	L-SP-200-865-89	6500	80	15085	169	
	L-SP-225-830-102	3000	80	16576	163	
<b>115W - 255cm</b>	L-SP-225-840-102	4000	80	17584	172	
	L-SP-225-850-102	5000	80	17472	171	
	L-SP-225-865-102	6500	80	17240	169	
<b>128W - 282cm</b>	L-SP-255-830-115	3000	80	18648	162	
	L-SP-255-840-115	4000	80	19782	172	
	L-SP-255-850-115	5000	80	19656	171	
<b>128W - 282cm</b>	L-SP-255-865-115	6500	80	19395	169	
	L-SP-282-830-128	3000	80	20720	162	
	L-SP-282-840-128	4000	80	21980	172	
<b>128W - 282cm</b>	L-SP-282-850-128	5000	80	21840	171	
	L-SP-282-865-128	6500	80	21550	168	

## Polar Intensity Diagram



**AFOI TSIOLAKI & SIA OE G.P.**  
Industrial Zone of Thessaloniki  
Greece  
T: +302310 798 335  
F: +302310 799 868

e-mail: [info@techlumen.gr](mailto:info@techlumen.gr)  
[www.techlumen.gr](http://www.techlumen.gr)

[facebook.com/Techlumen](https://www.facebook.com/Techlumen)  
[@Techlumen](https://www.instagram.com/Techlumen)  
[linkedin.com/company/tsiolakis-construction](https://www.linkedin.com/company/tsiolakis-construction)