



LED FLOODLIGHT -24V

SPC-24V Series

LED floodlight Techlumen SPC-24V is low in weight, minimal in design and small in size for its high power and efficacy.

It has various mounting options and can be easily installed in difficult positions.

SPC-24V is made of aluminium and painted with electrostatic paint. It is produced in a range of 50W - 150W versions.


It is equipped with optics that produce a beam of 30° to 120° or street lighting optics.

Optionally it can be made of anodised aluminium.




Dimensions


50W



100W



150W



Manufactured in Greece




Type	SPC-24V
Luminous Flux	6700 lm - 20160 lm
Power	50W - 150W
Input	24V DC
Ambient Temperature	-30 °C - + 50 °C
Efficacy	135 lm/W
CRI	70
CCT	5000K
IP Rating	IP68
Body	Alluminium
EPA	0.05 - 0.09 m2
Finishing	Powder coating - Any RAL
Dimensions	(300 - 500)mmX 150mm X 77mm
Weight	2.5 - 5.6Kg
Warranty	5 years


SPC-24V Versions					
Code	Watt	CCT	CRI	Lumen	Lm/W
SPC-24V-750-50	50W	5000	70	6720	135
SPC-24V-750-100	100W	5000	70	13440	135
SPC-24V-750-150	150W	5000	70	20160	135

Polar Intensity Diagram


30°




45°




60°




90°



120°



Wide



AFOI TSIOLAKI OE

Industrial Zone of Thessaloniki
Greece

T: +302310 798 335
F: +302310 799 868

e-mail: info@techlumen.gr
www.techlumen.gr

 facebook.com/Techlumen

 @Techlumen

 linkedin.com/company/tsiolakis-construction